

**MIEPL** FIT Series, Flow Rate Indicator cum Totalisers are designed for suitability in various industrial applications. These are used for indication and totalisation of flow. The input can be processed linearly or square rooted as per requirement of to indicate flow. Serial interface with RS-232 for PC and Printer Interface is optional.



### PRODUCT VERSION

**Dimensions(HXWXD)mm:**

**Display:**

FIT-1046	FIT-1049
96X96X100	96X96X100
<i>Upper:</i> RED	<i>Upper:</i> GREEN
6-Digit, 0.4"	9-Digit, 0.3"
<i>Lower:</i> GREEN	<i>Lower:</i> RED
4-Digit, 0.4"	4-Digit, 0.4"

**Display Range:**

4 Digits (0 - 9999 LPM, LPH, M<sup>3</sup>/Hr Selectable)

Correspond to Input

**Sensor Programming:**

Linear / Square Root

**Input:**

4 - 20 mA / 0 -10 VDC

**Pulses:**

5V DC Pulses

**Retransmission O/P (Optional):**

4 – 20 mA, 0 - 10V DC

**Output (Optional):**

Relay 5 Amp, 230V AC For Alarm or Trip Function

**Aux. Supply:**

24V DC

**Memory Retention:**

Non-Volatile Memory in case of Power Failure

**Power Supply:**

230V AC  $\pm$  20%, 50 Hz

**Cut Out (mm):**

92 X 92, 68 X 68, 44 X 92

**Mounting:**

Flush panel mounting with clamps fixed behind the panel.

### MILLENNIUM INSTRUMENTS LIMITED

**H.O. :** 101, 'Dwarkashish', Main Vikas Marg, Shakarpur, Delhi-92 (INDIA)

**Tel. :** +91-11-2201-4325, 4327, 65094516. **Fax.:** 22014326

**Website :** www.mil.org.in , www.miepl.com, **E-mail :** miepl@miepl.com

**Works :** F-12, Site-B, UPSIDC Ind. Area Surajpur, Greater Noida, Gautam Budh Nagar-201306 (U.P.) **E-mail :** sales@miepl.com, info@miepl.com